



DESCRIPTION AND USES

Port City Deck & Dock Wood Protector is a water-repellent protective treatment for new or weathered bare wood. It can be used on all types of exterior lumber to prevent the damaging effects of moisture such as splitting, swelling, and warping. It also helps prevent the growth of mildew, fungus, and algae.

Port City Deck & Dock Wood Protector is available in Clear, Butternut, Cedar, Cypress, and Mahogany colors. All colors, except Clear, contain UV light blocking pigments that help resist fading and discoloration (graying) caused by sunlight. The Clear formula will not prevent these color changes that occur naturally with an exposure to sunlight. This product is not recommended for use below ground level, for marine use, or on interior surfaces.

SPECIFICATIONS

SURFACE PREPARATION: All cutting, gluing, and sanding of the wood should be done before coating. Allow new pressure-treated wood to dry for at least 30 days. Wood must be clean and free of foreign material. If mildew is present, clean the surface with a 50% solution of household bleach and water. Discoloration can be removed and the wood restored to its natural color by using a wood brightener. Rinse well after these treatments. Wear protective gloves, clothing, and goggles when working with bleach or wood brightener. Allow at least 3 days drying time after rain or washing before finishing.

APPLICATION: Stir well. Apply with a brush or pad applicator. Do not roll or spray. Apply at a rate of 100-150 sq. ft. per gallon. Saturate the end grain. Do not over apply. Do not allow to puddle. **Port City Deck & Dock Wood Protector** must penetrate the wood. Apply 1 coat only. Protect plantings from spills and drips. Apply at temperatures above 40°F. Wear protective clothing and gloves when applying and handling coated boards.

MAINTENANCE: On horizontal surfaces with full exposure to the weather, such as decks, apply a yearly maintenance coat. On vertical surfaces such as siding, a maintenance coat should be applied every 2-3 years depending on exposure to the elements.

CLEAN UP: Clean tools with Paint Thinner (Mineral Spirits). Do not reuse empty container.

For complete safety information, refer to the MATERIAL SAFETY DATA SHEET for this product.

PRODUCT CODES

GALLONS

00535 - Clear
00536 - Cedar
00537 - Cypress
00538 - Butternut
00539 - Mahogany

QUARTS

00544 - Clear
00543 - Cedar
00542 - Cypress
00541 - Butternut
00540 - Mahogany

TECHNICAL DATA

VEHICLE TYPE: Alkyd Resin

VOLUME SOLIDS: 31%

WEIGHT SOLIDS: 35%

DENSITY: 7.2 lbs/gal

VOC: 4.6 lbs/gal

CLEAN UP SOLVENT: Paint Thinner (Mineral Spirits)

COVERAGE: 100 - 150 SF/gallon

DRY TIME: Complete dry in 24 hours

SHELF LIFE: 1 year shelf life when properly stored.

Port City Paints
1250 9th St.
Muskegon, MI 49440
www.portcitypaints.com

The suggestions for use and technical data here given are accurate to the best of our knowledge and are offered in good faith. Because the conditions and use of our products are beyond our control, our liability, if any, is limited to the replacement of defective material only. RepcoLite Paints, Inc. DISCLAIMS ALL OTHER WARRANTIES relating to our products and DISCLAIMS ALL WARRANTIES RELATING TO THEIR APPLICATION, expressed or implied, INCLUDING but not limited to warranties of merchantability and fitness for a particular purpose. TECHNICAL DATA IS SUBJECT TO CHANGE WITHOUT NOTICE.